



\*1: **SDS-M8** :  $d2 = \begin{smallmatrix} 0.1 \\ -0.3 \end{smallmatrix}$

● Material/Finish



	<b>SDS</b>
Main Body	SCM435 Equivalent (Hardness: 45HRC or Higher) Ferrosoferric Oxide Film (Black)



- The screw tip shape is a dog point.
- Use for positioning or as a rotation stopper by fitting the tip dog point shape into the counterpart groove or hole.

\*Dog point shape dimensions differ from JIS B 1177 for hex socket set screw long dog points.

## Dimensions

Unit : mm

Part Number ◀1	M (Coarse)		L1	d2	B	Mass (g)
	Nominal of Thread	Pitch				
<b>SDS-M3</b>	M3	0.5	2.5	2.5	1.5	0.4 - 0.7
<b>SDS-M4</b>	M4	0.7	3	3	2	0.8 - 2
<b>SDS-M5</b>	M5	0.8	4	4	2.5	1.3 - 3.3
<b>SDS-M6</b>	M6	1	5	4	3	1.5 - 6.2
<b>SDS-M8</b>	M8	1.25	6.5	6	4	3.3 - 12.5

Part Number	L (mm) ◀2									
	10	12	16	20	25	30	35	40	45	
<b>SDS-M3</b>	●	●	●	●						
<b>SDS-M4</b>		●	●	●	●	●				
<b>SDS-M5</b>		●	●	●	●	●				
<b>SDS-M6</b>		●	●	●	●	●	●	●		
<b>SDS-M8</b>			●	●	●	●	●	●	●	

● Part Number Specification

**SDS-M4-20**

◀1      ▶2

For ◀2 screw length L, select from the sizes marked with ● in the table.

Cleanroom Wash & Packaging Not Available	Screw Combination Available / Add'l charge	Screw Length Adjustment Not Available	Vibration Resistant Available / Add'l charge
---	---	--	---