



- For workpiece positioning and stopper applications.
- Pad is made of polyurethane. The material has excellent water resistance and has low risk of hydrolysis in humid environments.
- Urethane absorbs impacts.
- All products are provided with a lock nut.

• Material/Finish



	SUB
Thread Part	Steel Nickel Plating
Pad	Polyether Urethane (Hardness Shore A90) *1
Lock Nut	Steel Trivalent Chromate Treatment

*1 : While polyether urethane may show yellow discoloration, the performance remains unaffected.

Dimensions

Unit : mm

Part Number	M (Coarse)		L2	L1	D1	t	h	B	C	T	Mass (g)
	Nominal of Thread	Pitch									
SUB-M4	M4	0.7	3	2.8	5	1.5	1.5	7	8.1	2.4	2.1 - 4.1
SUB-M5	M5	0.8	3	3.5	6	1.5	1.5	8	9.2	3.2	3.3 - 6.6
SUB-M6	M6	1	3	4	8	2	2	10	11.5	3.6	6.3 - 11.7
SUB-M8	M8	1.25	3	5.5	10	2	2	13	15	5	12.7 - 23
SUB-M10	M10	1.5	3	7	13	2	2	17	19.6	6	24 - 39

Part Number	L (mm)							
	15	20	25	30	35	40	45	50
SUB-M4	●	●	●	●	●	●		
SUB-M5	●	●	●	●	●	●		
SUB-M6		●	●	●	●	●	●	●
SUB-M8		●	●	●	●	●	●	●
SUB-M10		●	●	●	●	●	●	●

- Part number specification

SUB-M4-35

Product Code **1** **2**

Cleanroom Wash & Packaging → P.xxxx	Screw Combination → P.xxxx	Screw Length Adjustment → P.xxxx	Vibration Resistant → P.xxxx
Not Available	Not Available	Available / Add'l charge	Available / Add'l charge